

## Semi Automatic Models



PW-316H

### Options

- Outside tension
- Air filter
- Stainless steel structure SUS #304
- Casters with brake



PW-616H

### PW-316H / PW-616H Semi-automatic Strapping Machine

Mechanical Tension Adjustment

H:High Profile

Power	1Ø, 110/220V, 50/60Hz
Strap Width	9, 12, 15 mm (adjustable) (6mm option)
Strapping Tension	15 ~ 50 Kgs
Strapping Speed	2.0 sec./strap
Strapping Size	Min. : 60 mm, Max. : Any size
PW-316H Table Height	750 mm
PW-616H Table Height	750 ~ 890 mm (Adjustable)
Machine Size	L 910 x W 580 x H 750 mm



PW-320H

### Options

- Air filter
- Stainless steel structure SUS #304
- Casters with brake



PW-620H

### PW-320H / PW620H Semi-automatic Strapping Machine

Electronic Tension Adjustment

H:High Profile

Power	1Ø, 110/220V, 50/60Hz
Strap Width	9, 12, 15 mm (adjustable) (6mm option)
Strapping Tension	5 ~ 50 Kgs
Strapping Speed	2.0 sec./strap
Strapping Size	Min. : 60 mm, Max. : Any size
PW-320H Table Height	750 mm
PW-620H Table Height	750 ~ 890 mm (Adjustable)
Machine Size	L 910 x W 580 x H 750 mm