



FAB/PH SERIES

FULLY AUTOMATIC ROTARY MEDICAL & PHARMACEUTICAL MACHINE



the STARVIEW ADVANTAGE

FAB/PH8-1418

INNOVATIVE PACKAGING MACHINES

Starview Packaging Machinery, Inc.

Toll Free: 888-278-5555 www.starviewpackaging.com sales@starviewpackaging.com

FAB/PH SERIES FULLY AUTOMATIC ROTARY MEDICAL & PHARMACEUTICAL MACHINE

YOUR MARKET ... OUR SOLUTIONS

The **FAB/PH Series** rotary type heat sealers are designed for medium to higher volume production requirements where automatic feeding and unloading is desired. These machines may be used for conventional carded blisters, full face blisters and half-clamshell styles as well as applications using medical paper, Tyvek, foils and other heat sealable lidstock. The **FAB/PH Series** units are available in six (6) and eight (8) station designs. Models are available in standard sealing areas of 14 x 18 inches and 18 x 24 inches. Larger sealing areas are available on request.

For machines capable of higher production rates please consider Starview's **CBS/PH** inline conveyor sealing machines.

the STARVIEW ADVANTAGE

- A wide range of standard and custom features available to match customer requirements.
- Generous use of stainless steel in the structure for the most durable finish in the industry.
- Color touch screen HMI for the ultimate in operator convenience and accessibility. Includes storage for 99 databases and on-screen data tracking.
- A Starview exclusive remote access via standard Ethernet hardwire or optional Wi-Fi router gives management access to real-time process information from the machine.
- On-screen temperature calibration standard with optional on-screen pressure calibration available to simplify validation using direct access validation ports.
- Ultra-high pressure sealing presses used in conjunction with matched aluminum tooling to give consistent sealing patterns with any heat sealable medical lidding materials. Hydro-pneumatic press available for cold seal materials.
- Precision indexing rotary table for precise sealing fixture to matching relieved face plate alignment.
- Industry leading design, construction, features and customer support.



FAB/PH SERIES SPECIFICATIONS

Electrical:

	FAB/PH6-1418	FAB/PH6-1824
Nominal sealing area:	14" x 18"	18" x 24"
Number of open stations:	2	2
Table index:	Automatic	Automatic
Heating system:	Multi Zones	Multi Zones
No. of automatic feeders:	2	2
Finished package unloader:	Standard	Standard
Standard blister/tray depth:	3.0"	3.0"
Average cycle speed:	1 – 18 cpm	1 — 14 cpm
Electrical:	208-230 Volts / 3 PH / 25 Amps	208-230 Volts / 3 PH / 45 Amps

	FAB/PH8-1418	FAB/PH8-1824
Nominal sealing area:	14" x 18"	18" x 24"
Number of open stations:	4	4
Table index:	Automatic	Automatic
Heating system:	Multi Zones	Multi Zones
No. of automatic feeders:	2	2
Finished package unloader:	Standard	Standard
Standard blister/tray depth:	3.0"	3.0"
Average cycle speed:	1 – 18 cpm	1 – 16 cpm

Specifications and model availability are subject to change without notice







208-230 Volts / 3 PH / 25 Amps

Please request specific model quotations for complete pricing, specifications and options from your local distributor. Feel free to contact Starview to obtain the contact information for the authorized distributor in your area.



208-230 Volts / 3 PH / 45 Amps

Starview Packaging Machinery, Inc.



